

KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KP-10015-1	100	3.7	5.8	15.0	22.0	2.8	15C	30C	3.5V
KP-20015-1	200	3.7	6.0	20.0	25.0	5.1	15C	30C	3.5V
KP-27015-1	270	3.7	7.0	20.0	30.0	6.9	15C	30C	3.5V
KP-40015-1	400	3.7	7.2	18.0	42.0	10.0	15C	30C	3.5V
KP-45015-1	450	3.7	3.8	30.0	48.0	13.0	15C	30C	3.5V
KP-45015-1	450	3.7	7.5	25.0	35.0	12.0	15C	30C	3.5V
KP-60015-1	600	3.7	5.5	30.0	48.5	16.0	15C	30C	3.5V
KP-60015-1	600	3.7	5.5	30.0	46.0	16.0	15C	30C	3.5V
KP-62015-1	620	3.7	4.0	33.0	62.0	17.0	15C	30C	3.5V
KP-65015-1	650	3.7	9.2	22.0	40.0	18.0	15C	30C	3.5V
KP-70015-1	700	3.7	6.2	17.0	89.0	18.0	15C	30C	3.5V
KP-70015-1	700	3.7	6.0	30.0	48.0	18.0	15C	30C	3.5V
KP-80015-1	800	3.7	6.8	30.0	48.0	19.0	15C	30C	3.5V
KP-85015-1	850	3.7	4.8	35.0	62.0	20.5	15C	30C	3.5V
KP-85015-1	850	3.7	7.2	30.0	48.5	20.5	15C	30C	3.5V
KP-90015-1	900	3.7	7.4	30.0	48.0	22.0	15C	30C	3.5V
KP-95015-1	950	3.7	6.5	20.0	100.0	23.0	15C	30C	3.5V
KP-1015-1	1000	3.7	4.0	30.0	90.0	25.0	15C	30C	3.5V
KP-1015-1	1000	3.7	5.6	35.0	62.0	24.0	15C	30C	3.5V
KP-1015-1	1000	3.7	8.2	30.0	48.5	24.0	15C	30C	3.5V
KP-1115-1	1100	3.7	9.0	30.0	48.0	26.0	15C	30C	3.5V
KP-1215-1	1200	3.7	5.2	34.0	80.0	28.0	15C	30C	3.5V
KP-1315-1	1300	3.7	7.2	35.0	62.0	31.3	15C	30C	3.5V
KP-1315-1S	1300	3.7	5.5	17.0	170.0	32.0	15C	30C	3.5V
KP-1315-1	1300	3.7	6.0	30.0	80.0	31.0	15C	30C	3.5V
KP-1315-1S	1300	3.7	5.5	20.0	120.0	32.0	15C	30C	3.5V

KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KP-1415-1	1400	3.7	5.0	34.0	96.0	33.0	15C	30C	3.5V
KP-1515-1	1500	3.7	6.0	34.0	80.0	36.0	15C	30C	3.5V
KP-1515-1	1500	3.7	8.0	35.0	62.0	35.0	15C	30C	3.5V
KP-1515-1	1500	3.7	7.6	30.0	80.0	36.0	15C	30C	3.5V
KP-1615-1	1600	3.7	6.7	42.0	58.0	38.0	15C	30C	3.5V
KP-1715-1	1700	3.7	7.0	34.0	80.0	42.0	15C	30C	3.5V
KP-1815-1	1800	3.7	6.5	32.0	96.0	42.0	15C	30C	3.5V
KP-1815-1	1800	3.7	6.0	34.0	96.0	42.0	15C	30C	3.5V
KP-1815-1	1800	3.7	8.5	30.0	80.0	42.0	15C	30C	3.5V
KP-1915-1	1900	3.7	7.2	30.0	90.0	43.0	15C	30C	3.5V
KP-2015-1	2000	3.7	6.8	34.0	96.0	48.0	15C	30C	3.5V
KP-2215-1	2200	3.7	7.2	34.0	96.0	50.0	15C	30C	3.5V
KP-2215-1	2200	3.7	9.0	34.0	80.0	51.0	15C	30C	3.5V
KP-2515-1	2500	3.7	6.0	34.0	125.0	57.0	15C	30C	3.5V
KP-3015-1	3000	3.7	7.8	34.0	125.0	68.0	15C	30C	3.5V
KP-3315-1	3350	3.7	10.0	34.0	104.0	73.0	15C	30C	3.5V
KP-3515-1	3550	3.7	7.4	56.0	90.0	77.0	15C	30C	3.5V
KP-4815-1	4800	3.7	8.0	48.0	135.0	109.0	15C	30C	3.5V
KP-5015-1	5000	3.7	5.5	60.0	150.0	113.0	15C	30C	3.5V
KP-03520-1	35	3.7	4.2	12.0	18.0	1.1	20C	40C	3.5V
KP-06020-1	60	3.7	4.5	13.0	22.0	1.8	20C	40C	3.5V
KP-07020-1	70	3.7	6.0	12.0	20.0	1.9	20C	40C	3.5V
KP-07520-1	75	3.7	6.3	14.0	18.0	2.2	20C	40C	3.5V
KP-07520-1	75	3.7	6.0	14.0	17.0	2.2	20C	40C	3.5V
KP-08020-1	80	3.7	5.0	17.0	17.0	2.3	20C	40C	3.5V
KP-10020-1	100	3.7	7.0	17.0	17.0	2.7	20C	40C	3.5V

KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KP-10020-1	100	3.7	4.5	15.0	28.0	3.1	20C	40C	3.5V
KP-10020-1	100	3.7	5.8	15.0	22.0	2.6	20C	40C	3.5V
KP-11020-1	110	3.7	7.5	17.0	18.0	3.0	20C	40C	3.5V
KP-12020-1	120	3.7	5.7	10.5	32.0	3.3	20C	40C	3.5V
KP-13020-1	130	3.7	5.5	12.0	30.0	3.2	20C	40C	3.5V
KP-13020-1	130	3.7	7.0	15.0	22.0	3.5	20C	40C	3.5V
KP-15020-1	150	3.7	5.7	11.0	40.0	4.0	20C	40C	3.5V
KP-15020-1	150	3.7	6.0	12.0	35.0	4.0	20C	40C	3.5V
KP-15020-1	150	3.7	6.8	17.0	23.0	4.0	20C	40C	3.5V
KP-15020-1	150	3.7	5.3	20.0	25.0	4.0	20C	40C	3.5V
KP-15020-1	150	3.7	3.5	15.0	45.0	4.0	20C	40C	3.5V
KP-18020-1	180	3.7	4.5	20.0	30.0	4.8	20C	40C	3.5V
KP-18020-1	180	3.7	6.0	20.0	25.0	4.8	20C	40C	3.5V
KP-18020-1	180	3.7	7.7	17.0	23.0	4.7	20C	40C	3.5V
KP-20020-1	200	3.7	5.5	20.0	30.0	5.2	20C	40C	3.5V
KP-20020-1	200	3.7	6.7	20.0	25.0	5.2	20C	40C	3.5V
KP-30020-1	300	3.7	8.0	20.0	30.0	7.5	20C	40C	3.5V
KP-35020-1	350	3.7	7.2	20.0	35.0	8.8	20C	40C	3.5V
KP-40020-1	400	3.7	6.8	22.0	40.0	11.0	20C	40C	3.5V
KP-45020-1	450	3.7	8.2	22.0	40.0	11.5	20C	40C	3.5V
KP-45020-1	450	3.7	8.7	20.0	35.0	11.5	20C	40C	3.5V
KP-48020-1	480	3.7	7.7	25.0	35.0	14.0	20C	40C	3.5V
KP-50020-1	500	3.7	6.0	23.0	50.5	14.0	20C	40C	3.5V
KP-53020-1	530	3.7	7.2	25.0	40.0	15.0	20C	40C	3.5V
KP-60020-1	600	3.7	5.0	30.0	52.0	17.0	20C	40C	3.5V
KP-70020-1	700	3.7	9.8	25.0	40.0	20.0	20C	40C	3.5V

KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KP-72020-1S	720	3.7	4.8	14.0	149.5	20.0	20C	40C	3.5V
KP-80020-1	800	3.7	6.0	25.0	62.0	21.0	20C	40C	3.5V
KP-80020-1	800	3.7	6.0	34.0	56.0	22.0	20C	40C	3.5V
KP-80020-1	800	3.7	6.8	30.0	52.0	22.0	20C	40C	3.5V
KP-85020-1	850	3.7	8.0	30.0	48.0	23.0	20C	40C	3.5V
KP-85020-1	850	3.7	7.5	30.0	48.5	23.0	20C	40C	3.5V
KP-1020-1	1000	3.7	7.2	30.0	60.0	25.0	20C	40C	3.5V
KP-1020-1	1000	3.7	6.0	35.0	62.0	27.0	20C	40C	3.5V
KP-1020-1S	1050	3.7	6.5	20.0	100.0	28.0	20C	40C	3.5V
KP-1120-1S	1100	3.7	6.7	20.5	95.0	26.0	20C	40C	3.5V
KP-1120-1	1150	3.7	9.2	30.0	52.0	26.5	20C	40C	3.5V
KP-1220-1S	1200	3.7	6.2	20.0	120.0	31.0	20C	40C	3.5V
KP-1220-1	1200	3.7	5.2	34.0	80.0	28.0	20C	40C	3.5V
KP-1320-1	1300	3.7	5.6	30.0	90.0	30.5	20C	40C	3.5V
KP-1320-1	1300	3.7	4.8	34.0	96.0	30.0	20C	40C	3.5V
KP-1320-1	1300	3.7	7.3	35.0	62.0	30.0	20C	40C	3.5V
KP-1520-1	1500	3.7	6.8	34.0	80.0	34.0	20C	40C	3.5V
KP-1520-1	1500	3.7	8.2	35.0	62.0	34.0	20C	40C	3.5V
KP-1620-1	1600	3.7	6.8	30.0	90.0	37.0	20C	40C	3.5V
KP-2020-1	2000	3.7	9.3	42.0	56.5	44.0	20C	40C	3.5V
KP-2120-1	2100	3.7	7.3	34.0	96.0	50.0	20C	40C	3.5V
KP-2220-1S	2200	3.7	6.2	36.0	120.0	53.0	20C	40C	3.5V
KP-2220-1	2200	3.7	7.5	34.0	96.0	53.0	20C	40C	3.5V
KP-2220-1	2200	3.7	7.5	34.0	106.0	53.0	20C	40C	3.5V
KP-2320-1	2300	3.7	4.8	43.0	128.0	55.0	20C	40C	3.5V
KP-2520-1	2500	3.7	5.5	42.0	125.0	61.0	20C	40C	3.5V

KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KP-2520-1	2500	3.7	5.0	43.0	128.0	59.0	20C	40C	3.5V
KP-2620-1	2600	3.7	8.2	34.0	106.0	60.0	20C	40C	3.5V
KP-2820-1	2800	3.7	7.2	36.0	120.0	66.0	20C	40C	3.5V
KP-3220-1	3200	3.7	6.0	48.0	135.0	77.0	20C	40C	3.5V
KP-3220-1	3200	3.7	7.0	42.0	125.0	77.0	20C	40C	3.5V
KP-3420-1	3400	3.7	8.5	36.0	120.0	76.0	20C	40C	3.5V
KP-3420-1	3400	3.7	7.8	45.0	135.0	82.0	20C	40C	3.5V
KP-3620-1	3600	3.7	7.0	45.0	135.0	87.0	20C	40C	3.5V
KP-3620-1	3600	3.7	7.3	43.0	128.0	87.0	20C	40C	3.5V
KP-3820-1	3850	3.7	7.5	43.0	128.0	85.0	20C	40C	3.5V
KP-4020-1	4000	3.7	9.8	35.5	120.0	88.0	20C	40C	3.5V
KP-4520-1	4500	3.7	7.6	43.0	150.0	108.0	20C	40C	3.5V
KP-4820-1	4800	3.7	8.2	43.0	150.0	124.0	20C	40C	3.5V
KP-5020-1	5000	3.7	8.5	43.0	150.0	118.0	20C	40C	3.5V