

## KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KP-1345-1	1300	3.7	8.0	35.0	62.0	37.0	50C	100C	3.5V
KP-1850-1	1800	3.7	7.2	34.0	96.0	50.0	50C	100C	3.5V
KP-2250-1	2200	3.7	8.5	34.0	106.0	59.0	50C	100C	3.5V
KP-2250-1	2200	3.7	8.4	34.0	96.0	62.0	50C	100C	3.5V
KP-2550-1	2500	3.7	6.0	43.0	128.0	68.0	50C	100C	3.5V
KP-2550-1	2500	3.7	9.5	34.0	96.0	67.0	50C	100C	3.5V
KP-2650-1	2600	3.7	9.0	34.0	106.0	68.0	50C	100C	3.5V
KP-2650-1	2600	3.7	9.8	34.0	96.0	68.0	50C	100C	3.5V
KP-3050-1	3000	3.7	7.1	42.0	125.0	81.0	50C	100C	3.5V
KP-3250-1	3200	3.7	7.0	45.0	135.0	86.0	50C	100C	3.5V
KP-3250-1	3200	3.7	7.5	43.0	128.0	85.0	50C	100C	3.5V
KP-3750-1	3700	3.7	8.0	42.0	124.5	101.0	50C	100C	3.5V
KP-4050-1	4000	3.7	8.0	43.0	150.0	109.0	50C	100C	3.5V
KP-4050-1	4000	3.7	8.5	45.0	135.0	108.0	50C	100C	3.5V
KP-4250-1	4200	3.7	8.2	45.0	135.0	113.0	50C	100C	3.5V
KP-4450-1	4400	3.7	9.5	43.0	128.0	117.0	50C	100C	3.5V
KP-4650-1	4600	3.7	8.5	43.0	150.0	119.0	50C	100C	3.5V
KP-4850-1	4800	3.7	9.5	43.0	150.0	128.0	50C	100C	3.5V
KP-5050-1	5000	3.7	9.2	43.0	150.0	132.0	50C	100C	3.5V
KP-5050-1	5000	3.7	7.8	45.0	180.5	136.0	50C	100C	3.5V
KP-5050-1	5000	3.7	9.5	48.0	135.0	131.0	50C	100C	3.5V
KP-5050-1	5000	3.7	9.0	43.0	150.0	132.0	50C	100C	3.5V
KP-5250-1	5200	3.7	10.5	43.0	150.0	138.0	50C	100C	3.5V
KP-6550-1	6500	3.7	9.5	45.0	180.5	190.0	50C	100C	3.5V