

KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KL-0060-1	60	3.7	4.0	12.0	20.0	1.8	1C	2C	3.5V
KL-0075-1	75	3.7	4.7	12.5	22.0	2.0	1C	2C	3.5V
KL-0120-1	120	3.7	4.0	20.0	21.0	2.8	1C	2C	3.5V
KL-0140-1	140	3.7	5.7	10.8	32.0	3.1	1C	2C	3.5V
KL-0150-1	150	3.7	4.0	20.0	25.0	3.4	1C	2C	3.5V
KL-0180-1	180	3.7	3.5	24.0	26.0	4.0	1C	2C	3.5V
KL-0200-1	200	3.7	6.0	15.0	28.0	4.5	1C	2C	3.5V
KL-0200-1	200	3.7	4.0	20.0	30.0	4.6	1C	2C	3.5V
KL-0220-1	220	3.7	4.0	15.0	45.0	4.8	1C	2C	3.5V
KL-0220-1	220	3.7	6.0	17.0	30.0	4.9	1C	2C	3.5V
KL-0240-1	240	3.7	6.0	20.0	25.0	5.1	1C	2C	3.5V
KL-0250-1	250	3.7	5.0	20.0	30.0	5.3	1C	2C	3.5V
KL-0260-1	260	3.7	4.5	15.0	43.0	5.3	1C	2C	3.5V
KL-0270-1	270	3.7	4.5	20.0	36.0	5.9	1C	2C	3.5V
KL-0300-1	300	3.7	6.0	24.0	25.0	6.2	1C	2C	3.5V
KL-0350-1	350	3.7	5.2	24.0	35.0	7.4	1C	2C	3.5V
KL-0390-1	390	3.7	5.0	12.0	71.0	8.0	1C	2C	3.5V
KL-0400-1	400	3.7	3.0	25.0	62.0	9.2	1C	2C	3.5V
KL-0400-1	400	3.7	5.5	22.0	40.0	8.2	1C	2C	3.5V
KL-0400-1	400	3.7	6.5	20.0	35.0	7.7	1C	2C	3.5V
KL-0400-1	400	3.7	6.7	12.0	61.0	9.5	1C	2C	3.5V
KL-0450-1	450	3.7	5.4	30.0	33.0	9.0	1C	2C	3.5V
KL-0450-1	450	3.7	7.5	25.0	30.0	9.0	1C	2C	3.5V
KL-0600-1	600	3.7	4.5	30.0	48.0	14.0	1C	2C	3.5V
KL-0600-1	600	3.7	9.0	25.0	30.0	14.0	1C	2C	3.5V
KL-0650-1	650	3.7	6.0	23.0	51.0	14.0	1C	2C	3.5V

KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KL-0650-1	650	3.7	7.5	15.0	57.0	14.5	1C	2C	3.5V
KL-0700-1	700	3.7	5.2	30.0	46.0	14.0	1C	2C	3.5V
KL-0730-1	730	3.7	8.0	30.0	33.0	15.0	1C	2C	3.5V
KL-0750-1	750	3.7	5.7	24.0	56.0	15.0	1C	2C	3.5V
KL-0800-1	800	3.7	5.0	34.0	48.0	17.0	1C	2C	3.5V
KL-0800-1	800	3.7	5.8	30.0	48.0	17.0	1C	2C	3.5V
KL-0850-1	850	3.7	5.0	34.0	50.0	18.0	1C	2C	3.5V
KL-0850-1	850	3.7	6.0	30.0	48.0	18.0	1C	2C	3.5V
KL-0900-1	900	3.7	6.5	30.0	46.0	19.0	1C	2C	3.5V
KL-0900-1	900	3.7	4.0	42.0	58.0	20.0	1C	2C	3.5V
KL-0900-1	900	3.7	8.5	29.5	38.0	19.0	1C	2C	3.5V
KL-1000-1	1000	3.7	6.2	30.0	55.0	20.0	1C	2C	3.5V
KL-1000-1	1000	3.7	6.0	34.0	50.0	21.0	1C	2C	3.5V
KL-1000-1	1000	3.7	7.2	30.0	48.0	21.0	1C	2C	3.5V
KL-1000-1	1000	3.7	3.0	50.0	69.0	20.0	1C	2C	3.5V
KL-1100-1	1100	3.7	7.5	30.0	48.0	20.0	1C	2C	3.5V
KL-1200-1	1200	3.7	5.0	23.0	104.0	24.0	1C	2C	3.5V
KL-1200-1	1200	3.7	6.5	36.0	50.0	22.0	1C	2C	3.5V
KL-1200-1	1200	3.7	7.0	32.0	55.0	22.0	1C	2C	3.5V
KL-1300-1	1300	3.7	6.2	35.0	62.0	26.0	1C	2C	3.5V
KL-1300-1	1300	3.7	3.5	47.0	82.0	26.0	1C	2C	3.5V
KL-1350-1	1350	3.7	3.7	50.0	69.0	26.0	1C	2C	3.5V
KL-1400-1	1400	3.7	7.7	36.0	50.0	27.0	1C	2C	3.5V
KL-1400-1	1400	3.7	8.0	34.0	48.0	26.0	1C	2C	3.5V
KL-1420-1	1420	3.7	9.5	30.0	48.0	27.0	1C	2C	3.5V
KL-1450-1	1450	3.7	4.5	38.0	85.0	28.0	1C	2C	3.5V

KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KL-1450-1	1450	3.7	6.0	20.0	120.0	27.0	1C	2C	3.5V
KL-1500-1	1500	3.7	9.2	34.0	48.0	30.0	1C	2C	3.5V
KL-1500-1	1500	3.7	8.0	36.0	52.0	31.0	1C	2C	3.5V
KL-1500-1	1500	3.7	4.6	45.0	66.0	29.0	1C	2C	3.5V
KL-1500-1	1500	3.7	10.5	23.0	62.0	28.0	1C	2C	3.5V
KL-1500-1	1500	3.7	10.2	30.0	48.5	28.0	1C	2C	3.5V
KL-1600-1	1600	3.7	7.2	35.0	62.0	31.0	1C	2C	3.5V
KL-1650-1	1650	3.7	8.3	36.0	52.0	31.0	1C	2C	3.5V
KL-1650-1	1650	3.7	6.2	42.0	58.0	31.0	1C	2C	3.5V
KL-1650-1	1650	3.7	4.0	40.0	104.0	34.0	1C	2C	3.5V
KL-1700-1	1700	3.7	9.5	34.0	50.0	34.0	1C	2C	3.5V
KL-1750-1	1750	3.7	10.0	37.0	46.0	35.0	1C	2C	3.5V
KL-1800-1	1800	3.7	5.0	54.0	68.0	34.0	1C	2C	3.5V
KL-1800-1	1800	3.7	10.2	34.0	50.0	32.0	1C	2C	3.5V
KL-1800-1	1800	3.7	4.5	28.0	135.0	36.0	1C	2C	3.5V
KL-1800-1	1800	3.7	4.8	48.0	84.0	36.0	1C	2C	3.5V
KL-2000-1	2000	3.7	8.7	35.0	62.0	40.0	1C	2C	3.5V
KL-2000-1	2000	3.7	4.5	50.0	95.0	40.0	1C	2C	3.5V
KL-2000-1	2000	3.7	4.2	45.0	100.0	40.0	1C	2C	3.5V
KL-2000-1	2000	3.7	5.7	50.0	69.0	40.0	1C	2C	3.5V
KL-2000-1	2000	3.7	6.2	32.0	96.0	40.0	1C	2C	3.5V
KL-2100-1	2100	3.7	5.0	48.0	84.0	41.0	1C	2C	3.5V
KL-2200-1	2200	3.7	5.8	28.0	135.0	43.0	1C	2C	3.5V
KL-2200-1	2200	3.7	8.5	30.0	80.0	42.0	1C	2C	3.5V
KL-2350-1	2350	3.7	6.8	50.0	60.0	44.0	1C	2C	3.5V
KL-2400-1	2400	3.7	6.8	38.0	85.0	44.0	1C	2C	3.5V

KongPower Li-Polymer Battery Type

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Max Discharge Current		
			T	W	L		Continuous Discharge Current	Burst Discharge Current	Cut-off Voltage (V)
KL-2500-1	2500	3.7	5.7	48.0	84.0	46.0	1C	2C	3.5V
KL-2600-1	2600	3.7	8.3	30.0	90.0	48.0	1C	2C	3.5V
KL-2700-1	2700	3.7	8.0	50.0	60.0	51.0	1C	2C	3.5V
KL-2900-1	2900	3.7	9.5	44.0	60.0	53.0	1C	2C	3.5V
KL-3000-1	3000	3.7	6.7	48.0	84.0	57.0	1C	2C	3.5V
KL-3000-1	3000	3.7	4.2	48.0	135.0	57.0	1C	2C	3.5V
KL-3000-1	3000	3.7	6.8	34.0	125.0	57.0	1C	2C	3.5V
KL-3100-1	3100	3.7	5.3	56.0	90.0	56.0	1C	2C	3.5V
KL-3100-1	3100	3.7	5.0	56.0	90.0	56.0	1C	2C	3.5V
KL-3200-1	3200	3.7	6.0	55.0	85.0	60.0	1C	2C	3.5V
KL-3200-1	3200	3.7	5.5	56.0	90.0	57.0	1C	2C	3.5V
KL-3200-1	3200	3.7	8.5	42.0	84.0	57.0	1C	2C	3.5V
KL-3300-1	3300	3.7	6.2	45.0	100.0	61.0	1C	2C	3.5V
KL-3300-1	3300	3.7	5.2	54.0	97.0	59.0	1C	2C	3.5V
KL-3400-1	3400	3.7	7.0	42.0	95.0	61.0	1C	2C	3.5V
KL-3400-1	3400	3.7	4.8	67.0	102.0	68.0	1C	2C	3.5V
KL-3600-1	3600	3.7	7.0	45.0	100.0	65.0	1C	2C	3.5V
KL-4000-1	4000	3.7	8.5	48.0	84.0	73.0	1C	2C	3.5V
KL-4000-1	4000	3.7	6.5	43.0	128.0	71.0	1C	2C	3.5V
KL-4000-1	4000	3.7	7.2	55.0	85.0	73.0	1C	2C	3.5V
KL-4200-1	4200	3.7	5.7	48.0	135.0	77.0	1C	2C	3.5V
KL-4500-1	4500	3.7	8.2	50.0	95.0	83.0	1C	2C	3.5V
KL-5000-1	5000	3.7	7.5	43.0	128.0	95.0	1C	2C	3.5V
KL-5000-1	5000	3.7	8.3	65.0	80.0	90.0	1C	2C	3.5V
KL-10000-1	10000	3.7	8.7	73.5	135.0	165.0	1C	2C	3.5V